

## PAW-TD23B6E5 (Edelstahl)



**Die umfangreiche Aquarea-Modellpalette  
bietet vielfältige Lösungen, mit denen  
Ihr Haus effizienter wird**

[WEITERE INFORMATIONEN](#)

Aquarea Tank		
Reference		PAW-TD23B6E5
Dimension (Height)	mm	1750
Dimension (Width)	mm	600
Dimension (Depth)	mm	646
Weight (empty)	Kg	111
Volume	L	230 + 60
Power supply (Voltage)	V	230
Power supply (Phase)		1
Power supply (Frequency)	Hz	50
Hot water tank - Volume	L	230
Hot water tank - Max working pressure	MPa (bar)	1,0 (10)
Hot water tank - Pressure test	MPa (bar)	1,5 (15)
Hot water tank - Max working temperature	°C	80
Hot water tank - Connections	mm	Ø22
Hot water tank - Material		EN 14521
Hot water tank - Insulation (Material)		PUR
Hot water tank - Insulation	t=mm	50
Hot water tank - Heating coil surface	m <sup>2</sup>	1,8
Hot water tank - Electrical heater	W	2800
Hot water tank - Energy loss at 65°C	kWh/24h	1,25
Hot water tank - Energy efficiency class (from A+ to F)		B
Hot water tank - Standing loss	W	52
Buffer tank - Volume	L	60
Buffer tank - Max working pressure	MPa (bar)	0,3 (3,0)
Buffer tank - Pressure test	MPa (bar)	0,39 (3,9)
Buffer tank - Max working temperature	°C	80
Buffer tank - Connections	mm	Ø22, copper
Buffer tank - Material		EN 14521
Buffer tank - Insulation (Material)		PUR
Buffer tank - Insulation	t=mm	50
Buffer tank - Heating coil surface	m <sup>2</sup>	—
Buffer tank - Electrical heater	W	—
Buffer tank - Energy loss at 65°C	kWh/24h	—
Buffer tank - Energy efficiency class (from A+ to F)		A
Buffer tank - Standing loss	W	29

## Zubehör